

# 1100 LITRE FLAT LIDDED CONTAINER: THE BEST IN ITS CLASS



UNIQUE DESIGN EASY HANDLING IMPROVED SAFETY

## Improved handling

- Easy grip handles on all sides
- For optimum manoeuvrability



## Increased safety

- Increased stability
- Increased safety when lifting





### **Material**

## Polymer components:


- □ Injection moulded from specially designed HDPE
- □ Resistant to decay, frost, heat and chemicals
- □ Special UV-stabilisers provide excellent ageing characteristics

## Corrosion resistant steel components:

- □ Wheel forks, wheel bearings, swivel brackets, lid retention springs and screws from galvanised steel. No maintenance necessary.
- Noise reduction:
- □ Wheel assemblies with solid rubber tyres
- Long service life:
- High quality materials
- Excellent manufacturing processes
- Even if exposed to high mechanical stress levels
- Recycling:
- ☐ All container parts are recyclable

# **Dimensions - Weights - Standards**

- Nominal volume:
- 1100 litres ■ Net weight: ca. 65 kg
- Max. load: 440 ka
- 510 kg Permitted total weight:



all dimensions according to EN 840













# Design

## **ADVANTAGES TO THE USER:**

- Easy handling through the use of ergonomic handles
- Versatile, with a comprehensive accessories range

#### **ADVANTAGES TO THE COLLECTOR:**

- Easy grip handles on all sides
- Employment of handles at the rear of the container
- Safe, easy handling, even with heavy loads
- Wide lifting trunnions for improved safety during lifting, even with awkward loads
- Various wheel assembly configurations for different applications
- Improved water drainage as a result of rounded lids
- Water drainage plug as standard
- Compatible with identification and weighing systems

# Colours

- Standard colours: grey, green, blue, yellow, brown, red
- Special colours are available on request
- All additives are cadmium free and environmentally friendly













# Imprints and markings

## **MARKING:**

- Manufacturer, year of manufacture, material
- Nominal volume, max. permitted total weight
- EN 840, RAL markings
- Individual markings with imprints, screen printing, hot-foil printing or adhesive labels

#### Accessories

For accessories and special design variations such as lid apertures, locks, towing brackets and fork lift sleeves, please refer to the separate accessories sheet for 4-wheeled containers



SULO Umwelttechnik GmbH & Co.KG Bünder Straße 85 D-32051 Herford Telefon +49 (0) 52 21 598-207

Telefax +49 (0) 52 21 598-579 Internet: www. sulo.com e-mail: info@sulo.de



Sulo MGB Ltd Lincoln Park Business Centre Lincoln Road Cressex Industrial Estate High Wycombe Bucks HP12 3RD

Tel: + 44 (0) 1494 511055 • Fax: + 44 (0) 1494 511044 Internet: www. sulo.com • E-mail: sales@sulo.co.uk